

# ROLA-TRAC LITE

Rola-Trac™ LITE offers a lightweight, budget-priced system and can be fitted on any surface to any shape, creating a firm, non slip surface for commercial, professional and domestic use.



**Rola-Trac Lite is a very versatile easy fit flooring system, which can be used on sites to create a wide range of solutions from temporary walkways, temporary flooring in tents and marquees to outside exhibitions & displays.**

Tried and tested by leading organisations such as the Ministry of Defence, numerous events, festivals and football stadia, Rola-Trac temporary walkways are ready and able to help you to get where you need to go and protect the ground they use for any event.

Rola-Trac Lite is quite probably the lightest and easiest to handle flooring of its type on the market, weighing in at just 2.25kg per m<sup>2</sup>. It is extremely easy and fast to install - one person can lay up to 70 square metres in an hour. This click together system can be put together in minutes and taken away even faster.

After you have finished using it, Rola-Trac Lite is easy to disassemble and store, inside or out, ready to use again whenever and wherever you need. If required, it can be easily cleaned with a quick hose down.

Rola-Trac Lite meets anti-slip regulations.



**Material:** PPCP

**Ambient Temperature range:** -40 to +50 °C

**Panel size:** 333mm x 166mm x 12mm

**Max Static Load:** Up to 15,000kg per m<sup>2</sup>

**UV Stability:** Resistant to UV damage

**Colour:** Available in a variety of different colours

**Panel thickness:** 12mm

**Resistance to corrosion:** We are not aware of any substance that would lead to the product corroding.

**Panel weight:** 0.125kg (2.25kg per m<sup>2</sup>)

**Resistance to petrol / oil derivatives:** Impervious to exposure of most substances. The only effect of such contact may be slight discolouration

**Suitable Surfaces:** Turf, Soil, Sand, Gravel, hard standing.

**External storage:** The product is suitable for outside, uncovered storage, the only impact being the possibility of slight fading of colour.

**Lateral inclines:** The product can support slopes and inclines of 20%.

**Permeable to liquid:** The product is not permeable to liquid. Liquid drains from the panel surface using designed holes.

\*Ground dependant.